



CHARLET special designs



Tractel Solutions offers a wide range of custom made sheaves
Pitch diameter ($\emptyset dp$) = Wire rope $\emptyset \times R$

If you have any special needs, please contact us:

Tractel Solutions S.A.S.

Phone: +33 4 78 50 18 18

Email: info.tractelsolutions@tractel.com



Pulleys, Blocks and Sheaves

BG – Cast iron roller

- Long service life
- Robust
- Adaptable, rebuildable (hub)
- Zinc bichromate

Model	Sheave Diameter (mm)	Wire Rope Diameter (mm)	WLL	Movement Back (mm)	Weight (gr)	Product Code
C034C11MU	34/40	9/11	100	8.2	90	83699
C042C12MU	42/50	10/12.6	160	10.2	170	83709
C054C17CU	54/63	15/17	250	12.3	200	83719
C063C17CM	63/80	16/18	400	12.5	320	83729
C080C19CM	80/100	17/19	630	19	680	83739
C0131C25MM	131/160	23/25	1,000	23	1500	83749



BH – Cast iron roller

- Long service life
- Robust
- Adaptable, rebuildable (hub)
- Zinc bichromate

Model	Sheave Diameter (mm)	Wire Rope Diameter (mm)	WLL	Movement Back (mm)	Weight (gr)	Product Code
C063C17CU	63/80	15/17	400	15	300	83759
C080C19CU	80/100	17/19	630	22	650	83769
C0131C25MU	131/160	23/25	1,250	30	1400	83779
C0161C34MU	161/200	32/34	2,000	30	2900	83789



BN – Polyamide roller

- Light
- Electrically insulated
- Corrosion resistant

Model	Sheave Diameter (mm)	Wire Rope Diameter (mm)	WLL	Ø	Weight (gr)	Product Code
C025C8PZ	25/32	6/8	63	6.3	5	83609
C032C10PZ	32/40	8/10	100	8.3	10	83619
C040C12PZ	40/50	10/12	160	10.3	20	83629
C044C7PZ	44/62	5/7.5	200	12.1	30	83639
C061C10PZ	61/76	8/10	300	12	60	83649
C066C8PZ	66/80	6/8	300	12.2	70	83659
C078C10PZ	78/100	6/8	300	12.2	90	83669
C078C12PZ	78/120	10/12	300	12.2	100	83679
C0118C12PZ	118/140	10/12	300	12.2	125	83689



Pulleys, Blocks and Sheaves

EH Snatch Block

- Snatch blocks for wire rope cables
- Zinc bichromated coating

Model	Sheave Diameter (mm)	Wire Rope Diameter (mm)	WLL	Weight (kg)	Product Code
E303H	80/100	8-9	1,000	3	80869
E347H	275/336	21-23	8,000	34	80949
E480H	275/336	14-16.3	6,400	34	81009
E333H	210/250	16-18	5,000	22	80929
E490H	160/200	13-15	5,000	17	81029
E470H*	160/200	10-11.5	3,200	18	80989
E323H	160/200	13-15	3,200	18	80909
E313H	132/160	10-12	2,000	8.5	80889
E460H*	132/160	7.5-8.3	1,600	7	80969
E305H	80/100	8-9	1,000	3	105489



EGZ Snatch blocks for wire rope cables

- Zinc bichromated coating
- Designed for temporary lifting or cable traction installations requiring quick installation and/or removal of the pulley

Model	Sheave Diameter (mm)	Wire Rope Diameter (mm)	WLL	Weight (kg)	Product Code
E303GZ	80/100	8/9	1,000	3	101829
E305GZ	80/100	8/9	1,000	3	252119
E460GZ	132/160	7.5/8.3	2,400	7	101839
E313GZ	132/160	10/12	2,000	8.5	105629
E470GZ	160/200	10/11.5	4,800	15.5	101849
E323GZ	160/200	13/15	3,200	15.5	192859
E490GZ	160/200	13/15	5,000	17	192869
E333GZ	210/250	16/18	5,000	22	192879
E480GZ	275/336	14/16.3	6,400	34	101859
E347GZ	275/336	21/23	8,000	34	192889



EJ - Pulley for wire rope

- Zinc bichromated coating
- Removable axle for easy sheave change and cable assembly

Model	WLL	Wire Rope Diameter (mm)	Sheave Diameter (mm)	Weight (kg)	Description	Product Code
E125J	1	8/9	80/100	1,9	Without hook / not dismountable	81049
E126J	0.63	8/9	80/100	2,6	With hook / dismountable	81059
E136J	1.25	10/11.5	132/160	5	With hook / dismountable	81099



Pulleys, Blocks and Sheaves



ELS = with safety hook



ELC = with safety clasp

ELC - ELS pulleys

New light & compact 1t pulley for use in Offshore applications or along with Minifor.

The pulley is designed to be as compact as possible for use in elevator cage ceiling, to install the elevator motor.

It is designed with the same principles than an ET pulley, in order to be robust, corrosion resistant (Zn coating) and with all elements being foolproof.

It exists in two version, ELC (as shown below) and ELS with safety hook (but less compact).

Model	Description	Sheave Diameter (mm)	Wire Rope Diameter (mm)	WLL	Weight (kg)	Product Code
ELC1-70E7	equipped with safety clasp	55	6.5/7	1,000	1.6	252209
ELS1-70E7	equipped with safety hook	55	6.5/7	1,000	1.8	252259



ETC Off-Shore Model Snatch Block

- Easy to set up
- Light
- Imperviousness of removable elements
- Intensive use

Model	Sheave Diameter (mm)	Wire Rope Diameter (mm)	WLL	Weight (kg)	Product Code
ETC2-79E10	60/79	9-10	2,000	2.7	81429
ETC5-114E14	90/114	12-14	5,000	8	81399
ETC5-165E14	140/165	12-14	5,000	10.5	81459
ETC8-142E19	112/142	17-19	8,000	15	81489
ETC8-209E19	177/209	17-19	8,000	20	81519
ETC8-262E19	221/262	17-19	8,000	25	81549
ETC8-326E23	275/326	20-23	8,000	29	81579
ETC12-145E23	112/145	20-23	12,500	30	81609
ETC12-216E23	174/216	20-23	12,500	35	81669
ETC12-216E29	174/216	26-29	12,500	35	81639
ETC15-262E23	221/262	20-23	15,000	38	81699
ETC15-326E23	275/326	20-23	15,000	45	81759
ETC15-420E23	355/420	20-23	15,000	65	81819
ETC20-216E29	174/216	26-29	20,000	39	81729
ETC20-268E38	224/268	35-38	20,000	56	81789
ETC20-410E38	349/410	35-38	20,000	70	81849
ETC25-262E29	221/262	26-29	25,000	62	81879
ETC25-326E29	270/326	26-29	25,000	85	81939
ETC32-334E46	270/334	42-46	32,000	95	81909
ETC32-518E46	443/518	42-46	32,000	135	81969

Pulleys, Blocks and Sheaves

ETM Off-Shore Model Snatch Block

- Easy to set up
- Light
- Imperviousness of removable elements

Model	Sheave Diameter (mm)	Wire Rope Diameter (mm)	WLL	Weight (kg)	Product Code
ETM2-79E10	60/79	9-10	2,000	2.7	81439
ETM5-114E14	90/114	12-14	5,000	8	81409
ETM5-165E14	140/165	12-14	5,000	10.5	81469
ETM8-142E19	112/142	17-19	8,000	15	81499
ETM8-209E19	177/209	17-19	8,000	20	81529
ETM8-262E19	221/262	17-19	8,000	25	81559
ETM8-326E23	275/326	20-23	8,000	29	81589
ETM12-145E23	112/145	20-23	12,500	30	81619
ETM12-216E23	174/216	20-23	12,500	35	81679
ETM12-216E29	174/216	26-29	12,500	35	81649
ETM15-262E23	221/262	20-23	15,000	38	81709
ETM15-326E23	275/326	20-23	15,000	45	81769
ETM15-420E23	355/420	20-23	15,000	65	81829
ETM20-216E29	174/216	26-29	20,000	39	81739
ETM20-268E38	224/268	35-38	20,000	56	81799
ETM20-410E38	349/410	35-38	20,000	70	81859
ETM25-262E29	221/262	26-29	25,000	62	81889
ETM25-326E29	270/326	26-29	25,000	85	81949
ETM32-334E46	270/334	42-46	32,000	95	81919
ETM32-518E46	443/518	42-46	32,000	135	81979



Pulleys, Blocks and Sheaves



ETA Off-Shore Model Snatch Block

- Easy to set up
- Light
- Imperviousness of removable elements

Model	Sheave Diameter (mm)	Wire Rope Diameter (mm)	WLL	Weight (kg)	Product Code
ETA 2-79E10	60/79	9-10	2,000	1.6	81449
ETA5-114E14	90/114	12-14	5,000	4.5	81419
ETA5-165E14	140/165	12-14	5,000	7	81479
ETA8-142E19	112/142	17-19	8,000	8.5	81509
ETA8-209E19	177/209	17-19	8,000	13.5	81539
ETA8-262E19	221/262	17-19	8,000	18	81569
ETA8-326E23	275/326	20-23	8,000	23	81599
ETA12-145E23	112/145	20-23	12,500	24	81629
ETA12-216E23	174/216	20-23	12,500	28	81689
ETA12-216E29	174/216	26-29	12,500	28	81659
ETA15-262E23	221/262	20-23	15,000	30	81719
ETA15-326E23	275/326	20-23	15,000	36	81779
ETA15-420E23	355/420	20-23	15,000	52	81839
ETA20-216E29	174/216	26-29	20,000	31	81749
ETA20-268E38	224/268	35-38	20,000	45	81809
ETA20-410E38	349/410	35-38	20,000	56	81869
ETA25-262E29	221/262	26-29	25,000	48	81899
ETA25-326E29	270/326	26-29	25,000	63	81959
ETA32-334E46	270/334	42-46	32,000	70	81929
ETA32-518E46	443/518	42-46	32,000	100	81989



FM - Wire Rope Blocks

- Non opening block for wire-rope
- This is the essential tool for tirlors and other pulling equipments
- Other models and dimensions on request

Model	WLL	Wire Rope Diameter (mm)	Sheave Diameter (mm)	Number of Sheaves	Weight (kg)	Description	Product Code
F003M	1.25	7/8	86/100	2	5	With hook - 2 sheaves	82289
F013M	3.2	10/11.5	140/160	2	12.5	With hook - 2 sheaves	82329
F023M	5	13/15	172/200	2	18	With hook - 2 sheaves	82369
F073M	5	10/11.5	140/160	3	16	With hook - 3 sheaves	82449

Pulleys, Blocks and Sheaves



CHB Two sheaves overhead craneblock

- Reinforced design.
- Fast production time
- Other dimensions on request

Model	Sheave Diameter (mm)	Wire Rope Diameter (mm)	WLL	Classification FEM/ISO	Weight (kg)	Product Code
CHB142M5	180/210	9/10	4	M5	27	105209
CHB142M6	180/210	9	4	M6	27	105219
CHB172M5	250/297	12/13	10	M5	65	105269
CHB172M6	250/297	12	8	M6	65	105279



CHA - Two sheaves overhead crane block

- Fast production
- Other dimensions on request

Model	Sheave Diameter (mm)	Wire Rope Diameter (mm)	WLL	Classification FEM/ISO	Weight (kg)	Product Code
CHA152M5	200/235	10/11	6.3	M5	45	105229
CHA152M6	200/235	10	5	M6	45	105239
CHA162M5	228/270	11/12	8	M5	64	105249
CHA162M6	228/270	11	6.3	M6	64	105259
CHA172M5	257/297	12/13	10	M5	76	105289
CHA172M6	257/297	12	8	M6	76	105299
CHA182M5	280/330	13/14	12.5	M5	120	105309
CHA182M6	280/330	13	10	M6	120	105319
CHA192M5	320/375	15/16	16	M5	152	105329
CHA192M6	320/375	15	12.5	M6	152	105339
CHA202M5	355/425	17/18	20	M5	215	105349
CHA202M6	355/245	17	16	M6	215	105359
CHA212M5	400/470	19/20	25	M5	270	105369
CHA212M6	400/470	19	20	M5	270	105379

EP Blocks for Man-Riding Applications

EP Blocks for Man-Riding Applications

Versatility

- EP sheaves can be used for both material lifting and man-riding with the same maximum working load.

Safety

- Pulleys in accordance with FEM87 and EN 1808
- Finger protection system
- Limit stop

Ease of use

- The particular geometry of the limit stop, developed by Tractel, allows a simple and quick insertion of the wire rope without tools.

Lightness

- The lightened flanges and the polyamide sheave make it light and easy to install.


Compatibility

- EP pulleys are compatible with our Tirfor and Tirak winch ranges for both material and man-riding applications.


Applications

- These pulleys are mainly designed for temporary cable lifting or pulling applications, when quick installation and/or removal of the pulley is necessary.
- They can be fixed to a mobile or fixed anchorage point having the required WLL.

Model	Sheave Diameter (mm)	Wire Rope Diameter (mm)	WLL	Weight (kg)	Product Code
EPA1.6-8/9 III	171/198	8-9	1.6 t	2.6	252739
EPA2.4-10/12 III	196/228.5	10-11.5	2.4 t	4.9	252789
EPA4.8-14/16 III	277.5/323.5	14-16.3	4.8 t	11.7	252839
EPC1.6-8-9 III	171/198	8-9	1.6 t	3.4	252699
EPC2.4-10/12 III	196/228.5	10-11.5	2.4 t	6.3	252749
EPC5-14/16 III	277.5/323.5	14-16.3	4.8 t	14.3	252799
EPE1.6-8/9 III	171/198	8-9	1.6 t	3.4	252709
EPE2.4-10/12 III	196/228.5	10-11.5	2.4 t	6.3	252759
EPE5-14/16 III	277.5/323.5	14-16.3	4.8 t	14.3	252809
EPF1.6-8/9 III	171/198	8-9	1.6 t	3.2	252719
EPF2.4-10/12 III	196/228.5	10-11.5	2.4 t	5.8	252769
EPF5-14/16 III	277.5/323.5	14-16.3	4.8 t	13.6	252819
EPL1.6-8/9 III	171/198	8-9	1.6 t	3.2	252729
EPL2.4-10/12 III	196/228.5	10-11.5	2.4 t	5.9	252779
EPL5-14/16 III	277.5/323.5	14-16.3	4.8 t	13.6	252829




EPA




EPC



EPE




EPF



EPL

Accessories for EP Blocks

Model	Description	Product Code
EP-MCP	Option remote installation	192969
EPBFC	Option limit detection stop	192959



Suspensions



CE – Swivel hook with safety catch

Model	WLL	Max. Opening (mm)	Weight (kg)	Product Code
C120E	0.8	19	0.5	104979
C121E	1	22	0.9	104989
C125E	1.5	22	0.9	104999
C126E	2.5	22	1.4	105009
C127E	3.2	25	1.7	105019
C128E	5.4	31	3.3	105029
C134E	8	41	6.8	105039
C135E	11	47	10	105049
C136E	16	53	15	105059
C137E	22	75	26	105069



CH – High resistance anchor shackle

- High resistance anchor shackle
- Bolt type anchor shackles with thin head bolt-nut, with cotter pin

Model	WLL	Max. Opening (mm)	Ø	Weight (kg)	Product Code
C036H/6	1	17	12	0.2	105599
C037H/6	1.5	18	14	0.22	105609
C039H/6	3.25	27	20	0.76	105589
C040H/6	4.75	32	22	1.2	105619
C041H/6	6.5	37	25	1.5	192269
C042H/6	8.5	43	30	2.5	192279
C043H/6	12	52	35	4.5	192289
C044H/6	13.5	57	38	6.6	192299
C100H/6	2	20	16	0.44	192648



CJ – Eye hook with safety catch

- Eye hook with safety catch
- Stamped hook
- Mainly fitted on sling or rope

Model	WLL	Max. Opening (mm)	Weight (kg)	Product Code
C091J	0.8	19	0.3	105079
C092J	1	19	0.45	105089
C101J	1.25	19	0.3	105109
C093J	1.6	24	0.6	105099
C102J	1.6	19	0.45	105119
C103J	2.5	24	0.6	105129
C104J	3.2	25	0.9	105139
C105J	5.4	30	1.6	105149
C106J	8	38	3.5	105159